

Spray Nozzles

Flat Spray Nozzles

Producing a uniform flat fan shaped pattern with tapering edges

TYPE AC SPRAY PATTERN



TYPICAL APPLICATIONS

Asphalt or tar laying, bottle washing, coal and gravel washing, degreasing, dishwashing, foam control, industrial washers, metal cleaning-rinsing and washing, spray coating, vehicle washing, water misting and water fountains.



AC Type Nozzle

One-piece male pipe thread design available in flow sizes from 2 – 600 with spray angles of 0, 25, 40, 50, 65, 80, 90°. Available in BSPT and NPT threads.

CAC Type Nozzle

Compact, one-piece male pipe thread design available in flow sizes from 2 – 300 with spray angles of 0, 25, 40, 50, 65, 80, 90°. See chart for thread sizes (1/16" size is NPT only).



LF Type Nozzle

Flanged tip design for use with standard threaded bodies and caps, available in flow sizes from 2 – 50 with spray angles of 0, 25, 40, 50, 65, 80, 90, 100 and 110°.

Body thread sizes 1/8", 1/4" & 3/8". See Accessories section.

LA Type

Large flanged tip design for use with threaded/welded bodies and caps, available in flow sizes from 10 – 200 with spray angles of 0, 25, 40, 50, 65, 80, 90°. Body thread sizes 1/2" & 3/4". See Accessories section.



AD Type Nozzle

Large dovetailed tip design for use with special threaded/welded bodies and caps, providing positive alignment. Available in flow sizes from 10 – 200 with spray angles of 0, 25, 40, 50, 65, 80, 90°. Orifice is offset 15° to axis of dovetail plus welded body in Stainless Steel. See Accessories section.

LD Type

Dovetailed tip design for use with special threaded/welded bodies and caps, providing positive alignment. Available in flow sizes from 2 – 50 with spray angles of 0, 25, 40, 50, 65, 80, 90°. Orifice is offset 5° to axis of dovetail plus welded body in Stainless Steel. See Accessories section.



Unless otherwise stated, all nozzles and tips are available in Brass and Stainless Steel as standard.

Contact our Helpline or your local distributor for further information
Tel: +44 (151) 424 6821 or inside USA Toll Free: 1-800 Delavan
E-mail: delavanspray@goodrich.com or sales@delavan.co.uk