

Solid Cone Nozzles

Producing uniform distribution across a wide pressure range

TYPICAL SPRAY PATTERN



TYPICAL APPLICATIONS


Aerating water, brine sprays, chemical processing, coil defrosting, dust control, evaporative condensers, evaporative coolers, industrial washers, roof cooling, spray coating, gas scrubbing and washing, cooling towers, coal washing, degreasing, gravel washing, dishwashing, foam control, industrial washing and water fountains.



BI Type Nozzle

BI 6 – 193 available. One-piece body with pressed in cross-milled core. Spray angles from 35° to 100° dependent upon flow size and pressure. See chart for available thread sizes.

BQ Type Nozzle





BN Type Nozzle

BN 6 – 200 available. One-piece body with pressed in cross-milled core. Spray angles from 85° to 135° dependent upon flow size and pressure. See chart for available thread sizes.

Unless otherwise stated, all nozzles and tips are available in Brass and Stainless Steel as standard.

BT Type Nozzle

BT 6 – 200 available. One-piece body with pressed in cross-milled core. Spray angles from 85° to 135° dependent upon flow size and pressure. See chart for available thread sizes.



Contact our Helpline or your local distributor for further information Tel: +44 (151) 424 6821 or inside USA Toll Free: 1-800 Delavan E-mail: delavanspray@goodrich.com or sales@delavan.co.uk